

GB CD 3P – “Drilling with Casing” Connection (CD 3P – Casing Drilling with 3-Pitch Thread)

Applications

- **Running** Standard Large OD Downhole Casing Applications.
- **Rotating** To Aid String Advancement.
- **Drilling** with Casing/**Drilling** with Liners.
- **Driving**

For use in non-abrasive environments.

Description


Specialty semi-premium connection machined from API Coupling Stock. The **GB CD 3P** Connection exceeds pipe body performance properties under all load combinations and is gas tight. Connection designed with 3-Pitch threadform for easy-stabbing, fast makeup without cross-threading. Innovative, triple taper thread design (box only) reduces localized bearing stresses in critical areas for improved fatigue resistance. Pin noses meet in the center for positive indication of proper field makeup. Pin noses, designed for **maximum bearing face area**, provide high torque resistance.

Features

- Uses GB 3P threads.
- Easy-stabbing, fast makeup without cross-threading.
- Meets API Coupling OD and Drift Diameter Specifications.
- Field proven in a variety of static and dynamic applications.
- Excellent make/break repeatability under field conditions.
- Enhanced fatigue life.
- Can be inspected with standard API Thread Gauges by any properly trained/experienced Third Party (special setting standards required).
- Positive makeup indication with pin nose engagement in center of connection. Also, has API Triangle Stamp on Pin for secondary makeup verification.
- Innovative Triple Taper Design reduces localized bearing stresses for enhanced fatigue resistance and reduced galling potential.
- High torque resistance.
- Drive-able.

Available

- Casing sizes 16” OD to 20” OD.
- All API Casing Grades and 16” OD through 20” OD Line Pipe; Grades X-56 and X-80.



GB CD 3P
US Patent 7,347,459

GB 3P Thread (3 Threads per inch)

